

P O L Y W E S T

SLEEVE SYSTEMS

Polyflex[®] RUBIN

cutting proofed - extremely stable - low weight

With our new future-oriented sleeve **RUBIN** we set the new benchmark for handling in operations.

These features describe the optimised sleeve with its innovative surface:

- ✓ cutting proofed
- ✓ extremely stable
- ✓ low weight

RUBIN is designed for every air-mandrel size and can be characterised by its good mounting behaviour.



RUBIN.... with fast service and short delivery time!

RUBIN.... the sum of experience !!

www.polywest.de

Tel. (+49) 2561 / 93 21- 0

Fax. (+49) 2561 / 93 21 40



Data sheet: Polyflex[®] RUBIN

Technical Data

Dimensions:

Wall-thickness: 1 to 72 mm

Design

Colour of surface: **red**

Hardness:

Hardness of surface: 75° shore D (DIN 53505)

Advantages

The new innovative surface is more cutting resistant, resistant to common inks and solvents (e.g. Acetone, Methyl ethyl keton). The specified construction enabled high quality printing results without axial vibration stripes due to sleeve. Adhesion of different tape types on this surface is very good (e.g. Lohmann, Tesa, 3M).

Application area

Specially developed for the use of uv- and water-based printing inks.

Also suitable for the use of solvent-based printing inks, if the customer is working according to the catalogue of measures of the "BG Druck und Papier" (Employer's Liability Insurance Association – Paper & Print). Otherwise we recommend the use of ONYX sleeves (antistatic).